



SKU	Designation	French Law	Length (cm)	Weight (g)	MSRP
PHO6G302	GRS Bifrost - Stock for Howa 1500 R/H Short Action rifles.	Vente libre	80	1350	849.00 € incl. tax 424.50 € incl. tax

**Fully adjustable fiberglass reinforced stock for Howa 1500 R/H Short Action rifles.**

The new Bifrost stock is made from a sturdy fiberglass-reinforced material that can withstand harsh impacts and all kinds of weather conditions. Rubberized grip surfaces provide a firm grip whatever the conditions.

- Rifle dimensions: 30.4" in length
- Suitable for Howa 1500 SA
- Right-handed

This installation is described for a standard bolt-action rifle. (Tikka T3, Sako 85/75, Remington 700, Howa 1500):

- Making sure the rifle is unloaded, remove the slide from the rifle.
- Loosen and remove the action screw behind the trigger guard and the front action screw.
- Remove the bottom metal.
- Pull the barrel out of the stock.
- Place the barrel in the GRS stock, on the Tikka and Sako models, and make sure that the support block finds its place in the slot located under the barrel. If not, you will see that the action and barrel are not parallel to the stock and barrel channel.
- Place the bottom metal in the GRS stock, make sure the magazine (Remington, Howa models) is correctly seated in the bottom metal.
- Insert the front and rear action screws and tighten them loosely.
- Tighten the front screw to 3.5 NM (31 inch-pounds).
- Tighten the rear screw to 3.5 NM (31 inch-pounds).
- Inspect the action and barrel in the stock, do they look parallel? Is the hinged bottom metal working as it should? If you notice any irregularities, check that the magazine is seated correctly in the bottom metal.
- Put the slide into the rifle, make sure it is not loaded. Operate the slide and dry fire.
- Verify that security is working properly.

*Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.*