



https://armsco.fr//en/produit-20732-AR10-Bolt-Head-Segments-Set-of-3





SKU	Designation	French Law	MSRP
YDB15-01	Complete extractor AR15 7.62X39	Vente libre	40.00 € incl. tax

# Ensure reliable extraction of 7.62x39 caliber cases on your DB15 with this complete, ready-to-install extractor.

This complete extractor is specifically designed for Diamondback DB15 rifle bolts chambered in 7.62x39. It includes the machined extractor, spring, insert, O-ring, and retaining pin. Each component is calibrated to work perfectly with the specific pressures of the Russian caliber, ensuring consistent extraction even with steel or surplus cartridges.

■ Compatibility: Diamondback DB15 7.62x39

■ **Caliber**: 7.62x39 mm

**■** Composition :

■ Treated steel extractor

■ Spring + insert

O-ring

■ Retaining pin

■ **Surface treatment** : Nitriding or phosphating (depending on batch)

■ **Mounting** : Direct into the DB15 cylinder head

■ **Standards**: Complies with specific AR 7.62 specifications

## Function of a complete extractor

The extractor is responsible for removing the case from the chamber after firing. The spring, insert, and Oring maintain a constant pressure adapted to the specific geometry of 7.62x39 cases. On DB15s, an improperly adapted extractor configuration can lead to incomplete extractions or even case ruptures.

#### Adaptation to 7.62x39 caliber

Unlike .223 extractors, this model features a **widened and reinforced claw profile**, specifically designed for the taper of 7.62 cases. It is also reinforced to withstand corrosion associated with varnished steel or military surplus ammunition.

## Materials and durability

The extractor is machined from **high-strength steel**, heat-treated to maintain its elasticity and hardness despite fouling or high temperatures. The spring is coupled with a rigid insert and a high-density O-ring, ensuring firm retention even with low-pressure ammunition.

## **Maintenance and replacement**

Recommended every 5,000 to 7,000 shots, this kit allows for rapid reconditioning of the bolt. Replacement is simple: remove the pin, insert the complete extractor, and replace the pin.

Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.