



Plus de visuels disponibles sur le site



SKU	Designation	French Law	Height (cm)	Weight (g)	Mounting	MSRP
SW43501	down	Vente libre	1.4	12	21mm rail	90.00 € incl. tax
SW43202	high	Vente libre	2.7	22	-	90.00 € incl. tax

Position your red dot at 12 o'clock on your FUSE one-piece mount.

The **Scalarworks KICK/09** is a rail extension designed to accommodate magnifiers and laser modules on a compact platform, with perfect alignment and a controlled footprint.

- **Configurations:** Magnifier, Laser, Combo Laser + Magnifier
- **Material:** 7075-T6 Aluminum
- **Finish:** Type III anodizing
- **Height under lens:** 1.57" (? 39.9 mm)
- **Height:** SW4200: 14 mm
- **Height:** SW4220: 27 mm
- **Weight:** 12 to 22 g depending on the version
- **Origin:** United States

Box contents

- **Media:** Scalarworks® KICK/06™
- **Screws:**
 - (2) #6-32 x 0.4375" Nylon Pan Head Screw
 - (2) M4 x 0.7 nylon socket head cap screw
- **Tools :**
 - Scalarworks® T15 Torx Bit
 - Scalarworks® T20 Torx Bit

A red dot in the 12 o'clock position for instant acquisition

The **Scalarworks KICK/08** allows for the integration of a **red dot sight** directly above the main optic. In practice, a slight tilt of the head is all it takes to switch from magnification to rapid aiming, without changing the shooting position. This configuration is particularly appreciated for its improved responsiveness.

Two heights for a precise adjustment

Available in **low (SW4200 - 14 mm)** and **high (SW4220 - 27 mm)** versions, this mount allows you to perfectly adapt the red dot's position to your setup. This choice directly influences visual comfort and acquisition speed—a detail that makes all the difference in the field.

Extended compatibility with micro red dots

The **KICK/08** is designed to accommodate popular optics such as the **Leupold DeltaPoint Pro** , **RMSc** standard models, as well as modern options like the **Eotech EFLX** or the **Vortex Defender** . It integrates perfectly with **Scalarworks FUSE** mounts, ensuring mechanical and aesthetic consistency.

Robust construction and lightweight

Made from **7075-T6 aluminum** with **4140H steel** components, this bracket combines lightness and strength. **Type III** anodizing and **Flash Nitride** treatment ensure excellent durability. Weighing only **12 to 22 g** , it is virtually unnoticeable once installed.

FAQ

Is this setup compatible with all red dots?

It is compatible with DeltaPoint Pro and RMSc standard optics, as well as several Eotech and Vortex models.

Which height should I choose between the low and high versions?

The low version promotes a compact design, while the high version improves visual comfort depending on your configuration.

Is it compatible with all Scalarworks setups?

It is designed to work with Scalarworks FUSE/02 to FUSE/05 assemblies.

Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.