



**SCALARWORKS**

SKU	Designation	French Law	Diam. (mm)	Height (cm)	Weight (g)	Mounting	MSRP
SW315157	height 1.57"	Vente libre	35	4	154	21mm rail	480.00 € incl. tax

### Ultra-rigid 35mm mount for modern LPVO optics.

The **Scalarworks FUSE/04** is a one-piece 35mm mount designed to offer rigidity, precision and ease of installation on **Picatinny** rail, perfectly suited for LPVO and long-range optics.

- **Ring diameter:** 35 mm
- **Rail compatibility:** MIL-STD-1913 Picatinny
- **Optical axis height:** 1.57" (40 mm)
- **Tilt:** 0 MOA
- **Extension compatibility:** KICK/01, KICK/06, KICK/07, KICK/08
- **Weight:** 154 g
- **Materials:** 7075-T6 Aluminum / 4140H Steel
- **Finish:** Type III Anodizing / Flash Nitride
- **Origin:** United States

### Box contents

- **Media:** Scalarworks® FUSE/04™
- **Screws:**
  - (12) #8-40 screw with nylon patch
- **Tools :**
  - Scalarworks® T15 Torx Bit
  - Scalarworks® T25 Torx Bit
  - Scalarworks® LevelDrive® Tool

**A mount specifically designed for modern 35mm lenses**

The **Scalarworks FUSE/04** was designed to accommodate **LPVO** optics and high-magnification telescopes with a **35mm** diameter. From the moment of installation, the simplicity of the bolt-on system is appreciated, combined with remarkable rigidity that inspires confidence in demanding setups.

### **LEVEL DRIVE adjustment tool**

Each mount comes with its own level drive tool. This tool is installed in the one-piece mount to ensure perfect alignment between the scope and the mount. A bubble level is not required.

### **Rigidity and optimized design**

Its one-piece construction in **7075-T6 aluminum** , combined with **4140H steel** components, guarantees excellent mechanical strength. The entire assembly is treated with **Type III** anodizing and a **Flash Nitride** coating, ensuring durability and resistance to intensive conditions.

### **Scalable platform with 12 o'clock mounting**

The **FUSE/04** allows you to add a **secondary red dot sight** at the **12 o'clock** position using **KICK** extensions. It is compatible with the **KICK/06** (RMR footprint), **KICK/07** (ACRO), **KICK/08** (DPP/RMSc), and **KICK/01** for a **Picatinny Dive Board** interface. An ideal solution for increased versatility without requiring multiple setups.

### **Optimized ergonomics and height**

With an optical axis height of **1.57" (40 mm)** , this mount offers a natural and comfortable alignment, promoting rapid acquisition and a stable posture. On the field, this type of geometry quickly makes a difference in terms of fluidity.

### **FAQ**

#### **Is this mount compatible with all 35mm scopes?**

Yes, it is designed for optics with a 35mm tube, subject to dimensional compatibility.

#### **Can a secondary red dot be added?**

Yes, via the **KICK/01**, **KICK/06**, **KICK/07** and **KICK/08** extensions in the 12 o'clock position.

#### **Which rails is it compatible with?**

It is compatible with MIL-STD-1913 Picatinny standard rails.

*Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.*